

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

16300074

REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

- | | |
|-------------------------------|--|
| 1. RATED VOLTAGE | 5.00 ±.01 VOLTS D.C. |
| 2. CURRENT | 1.79 ±5% AMPS |
| 3. COLOR TEMPERATURE | 2915 °K (USING A TELESCOPING OPTICAL PYROMETER) |
| 4. MEAN SPHERICAL CANDLEPOWER | 7.20 ±10% MSCP (WIRE TERMINAL LAMP IN A 12" INTEGRATING SPHERE) |
| 5. SPOT SIZE | .225 NOMINAL DIAMETER MEASURED IN A TRANSVERSE PLANE TANGENT TO THE LENS |
| 6. FILAMENT TYPE | C-6 |
| 7. DESIGN LIFE | 6000 HOURS AVERAGE (LAB RATED) |

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN	DATE	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			PMB	9/26/84				
BASIC DIMENSION	.XX	.XXX	CHECKED	9/26/84	TITLE: LAMP SPECIFICATIONS FOR 998319-15			
UP TO 6	±.02	±.005	RAD	9/26/84				
ABOVE 6 TO 24	±.03	±.010	APPROVED	9/26/84	CODE IDENT	DRAWING NO. 16300074	REV.	
ABOVE 24	±.06	±.015	DAB	9/27/84	64475			
ANGLES ± 1/2 DEGREE			REL. FOR PROD. DRW	9/27/84	DO NOT SCALE			
					SHEET			OF