

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300113		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT, TUNGSTEN
HALOGEN REGENERATIVE CYCLE, MINIATURE
TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

6.00 ±.01 VOLTS D.C.

3. CURRENT

1.67 ±5% AMPERES

4. COLOR TEMPERATURE

3215 °K AT FILAMENT CENTER COILS OUTER
DIAMETER USING A TELESCOPING OPTICAL
PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


16.5 ±12% MSCP (WIRE TERMINAL LAMP IN A
20" INTEGRATING SPHERE)

6. DESIGN LIFE

100 HOURS AVERAGE

7. LIGHT CENTER LENGTH

.768 +/-.020 L.C.L.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB	DATE 3/23/87	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED JWH	3/23/87	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01110			
BASIC DIMENSION	.XX	.XXX	APPROVED DAB	3/23/87	CODE IDENT 64475		DRAWING NO. 16300113	REV.
UP TO 6	±.02	±.005	REL. FOR PROD. DRW	4/3/87	SCALE			
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE				SHEET OF	
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								