

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300114		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT,
TUNGSTEN HALOGEN REGENERATIVE CYCLE,
MINIATURE TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

6.00 ±.01 VOLTS D.C.

3. CURRENT

3.35 ±5% AMPS

4. COLOR TEMPERATURE

3325 °K AT FILAMENT CENTER COILS
OUTER DIAMETER, USING A TELESCOPING
OPTICAL PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


37.0 ±12% MSCP (WIRE TERMINAL LAMP
MEASURED IN A 20" INTEGRATING SPHERE)

6. DESIGN LIFE

100 HOURS AVERAGE

7. LIGHT CENTER LENGTH

.768 ±.020 L.C.L.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB	DATE 3/23/87	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED JWH	3/23/87	TITLE: LAMP SPECIFICATOINS FOR SK-DAB-01111			
BASIC DIMENSION	.XX	.XXX	APPROVED DAB	3/23/87				
UP TO 6	±.02	±.005	REL. FOR PROD. DRW	4/3/87				
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		CODE IDENT 64475		DRAWING NO. 16300114	REV.
ABOVE 24	±.06	±.015			SCALE		SHEET OF	
ANGLES ± 1/2 DEGREE								