

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL
B	RELEASE IN SAP	101-3112	12/10/07	RAD

- | | |
|-------------------------------|---|
| 1. LAMP TYPE | HEMISPHERICAL END, C-6 FILAMENT, TUNGSTEN HALOGEN
REGENERATIVE CYCLE, MINIATURE TWO-PIN CONSTRUCTION |
| 2. RATED VOLTAGE | 14.0 $\pm$.01 VOLTS D.C. |
| 3. CURRENT | 1.79 $\pm$ 5% AMPERES |
| 4. COLOR TEMPERATURE | 3200 °K AT FILAMENT CENTER COILS
OUTER DIAMETER USING A TELESCOPING
OPTICAL PYROMETER |
| 5. MEAN SPHERICAL CANDLEPOWER | 44.0 $\pm$ 12% MSCP (WIRE TERMINAL LAMP IN A
20" INTEGRATING SPHERE) |
| 8. DESIGN LIFE | 200 HOURS AVERAGE |
| 7. LIGHT CENTER LENGTH | .768 $\pm$.020 L.C.L. |

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB	DATE	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED		TITLE:			
BASIC DIMENSION	.XX	.XXX	JWH	4/20/87	LAMP SPECIFICATIONS FOR 01125-U			
UP TO 6	±.02	±.005	APPROVED DAB	5/13/87				
ABOVE 6 TO 24	±.03	±.010	REL. FOR PROD. DAB	5/13/87	CODE IDENT 64475	A	DRAWING NO. 16300123-U	REV. B
ABOVE 24	±.06	±.015	DO NOT SCALE		SCALE		SHEET OF	
ANGLES ± 1/2 DEGREE								