


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300125		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE	HEMISPHERICAL END, C-6 FILAMENT, TUNGSTEN HALOGEN REGENERATIVE CYCLE, MINIATURE TWO-PIN CONSTRUCTION
2. RATED VOLTAGE	10.5 ±.01 VOLTS D.C.
3. CURRENT	1.50 ±5% AMPERES
4. COLOR TEMPERATURE	2820 °K AT FILAMENT CENTER COILS OUTER DIAMETER USING A TELESCOPING OPTICAL PYROMETER
5. MEAN SPHERICAL CANDLEPOWER	15.0 ±12% MSCP (WIRE TERMINAL LAMP IN A 20" INTEGRATING SPHERE)
8. DESIGN LIFE	5000 HOURS AVERAGE (LAB RATED)
7. LIGHT CENTER LENGTH	.768 ±.020 L.C.L.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN <i>PMB</i>	DATE	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED <i>JWH</i>	5/12/87	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01126			
BASIC DIMENSION	.XX	.XXX	APPROVED <i>DAB</i>	5/13/87	CODE IDENT 64475		DRAWING NO. 16300125	REV.
UP TO 6	±.02	±.005	REL. FOR PROD. <i>DAB</i>	5/13/87	SCALE		SHEET OF	
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE					
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								