

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

			16300170		C
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL	
B	ADDED TO RATED VOLTAGE, VOLTS A.C., 60 HZ OR D.C.	3-1260	8/25/94	DAB	
C	2500 HRS. WAS 2000	3-1271	10/6/94	DAB	

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT, TUNGSTEN HALOGEN REGENERATIVE CYCLE, MINIATURE TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

6.00 ±.01 VOLTS A.C., 60 HZ OR D.C.

3. CURRENT

3.28 ±5% AMPERES

4. COLOR TEMPERATURE

3050 °K AT FILAMENT CENTER COILS OUTER DIAMETER USING A TELESCOPING OPTICAL PYROMETER

5. MEAN SPHERICAL CANDLEPOWER

24.0 ±12% MSCP (TWO PIN LAMP IN A 20" INTEGRATING SPHERE)

6. DESIGN LIFE

2500 HOURS AVERAGE

7. LIGHT CENTER LENGTH

.768 +/-.020 L.C.L.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN	DATE	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.				
TOLERANCES ON:			PMB	4/24/89	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01164				
BASIC DIMENSION	.XX	.XXX	CHECKED	MCA					4/26/89
UP TO 6	±.02	±.005	APPROVED	DAB	5/10/89	CODE IDENT 64475			
ABOVE 6 TO 24	±.03	±.010	REL. FOR PROD.	DRW	5/11/89				
ABOVE 24	±.06	±.015	DO NOT SCALE		DRAWING NO. 16300170		REV. C		
ANGLES ± 1/2 DEGREE									
			SCALE				SHEET OF		