

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300200		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL
A	FILAMENT DESIGN CHANGE; SEE ECN	3-1121		

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT,
TUNGSTEN HALOGEN REGENERATIVE
CYCLE, MINIATURE TWO-PIN
CONSTRUCTION

2. RATED VOLTAGE

4.70 ±.01 VOLTS D.C.

3. CURRENT

3.85 ±5% AMPERES

4. COLOR TEMPERATURE

3340 °K AT FILAMENT CENTER COILS OUTER
DIAMETER USING A TELESCOPING OPTICAL
PYROMETER

5. MEAN SPHERICAL CANDLEPOWER

32.7 ±12% MSCP (WIRE TERMINAL LAMP IN A
20" INTEGRATING SPHERE)

6. DESIGN LIFE

75 HOURS AVERAGE

7. LIGHT CENTER LENGTH

.768 ±.020 L.C.L.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN LWW	DATE 1/24/91	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED JWH	2/13/91	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01183			
BASIC DIMENSION	.XX	.XXX	APPROVED RAD	2/15/91	CODE IDENT 64475	△	DRAWING NO. 16300200	REV. A
UP TO 6	±.02	±.005	REL. FOR PROD. DAB	2/15/91	SCALE			
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE				SHEET OF	
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								