

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300320		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

LENSED END, C-6 FILAMENT, TUNGSTEN
HALOGEN REGENERATIVE CYCLE,
MINIATURE TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

12.00 ±.01 VOLTS D.C.

3. CURRENT

1.00 ±5% AMPERES

4. COLOR TEMPERATURE

3280 °K AT FILAMENT CENTER COILS OUTER
DIAMETER USING A TELESCOPING OPTICAL
PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


22.0 ±12% MSCP (WIRE TERMINAL LAMP IN A
20" INTEGRATING SPHERE)

6. DESIGN LIFE

40 HOURS AVERAGE (LAB RATED)

7. SPOT SIZE

.195" NOMINAL DIA. MEASURED IN A TRANSVERSE
PLANE TANGENT TO THE LENS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB	DATE 7/27/94	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED RAD	7/27/94	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01191			
BASIC DIMENSION	.XX	.XXX	APPROVED JCS	8/3/94	CODE IDENT 64475		DRAWING NO. 16300320	REV.
UP TO 6	±.02	±.005	REL. FOR PROD. DAB	8/3/94	SCALE		SHEET OF	
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE					
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								