

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300325		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT, TUNGSTEN
HALOGEN REGENERATIVE CYCLE, MINIATURE
TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

6.00 ±.01 VOLTS A.C., 60 HZ OR D.C.

3. CURRENT

3.28 ±5% AMPERES

4. COLOR TEMPERATURE

3050 °K AT FILAMENT CENTER COILS OUTER
DIAMETER USING A TELESCOPING OPTICAL
PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


24.0 ±12% MSCP (TWO PIN LAMP IN A
20" INTEGRATING SPHERE)

6. DESIGN LIFE

2500 HOURS AVERAGE

7. LIGHT CENTER LENGTH

.768 +/-.020 L.C.L.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB	DATE 10/4/94	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED WKM	10/5/94	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01268			
BASIC DIMENSION	.XX	.XXX	APPROVED RAD	10/5/94	CODE IDENT 64475		DRAWING NO. 16300325	REV.
UP TO 6	±.02	±.005	REL. FOR PROD. DAB	10/6/94	SCALE		SHEET OF	
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE					
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								