


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300334		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE	HEMISPHERICAL END, C-6 FILAMENT, TUNGSTEN HALOGEN REGENERATIVE CYCLE, MINIATURE TWO-PIN CONSTRUCTION
2. RATED VOLTAGE	7.20 ±.01 VOLTS D.C.
3. CURRENT	2.77 ±5% AMPERES
4. COLOR TEMPERATURE	3320 °K DESIGN AVERAGE AS MEASURED WITH AN ORIEL CORPORATION DIODE ARRAY RADIOMETER, MODEL INSTASPC III, EQUIPPED WITH A 8" INTEGRATING SPHERE
5. MEAN SPHERICAL CANDLEPOWER	44.0 ±12% MSCP (WIRE TERMINAL LAMP IN A 20" INTEGRATING SPHERE)
6. DESIGN LIFE	40 HOURS AVERAGE (LAB RATED)
7. LIGHT CENTER LENGTH	.768 ±.020 L.C.L.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN <i>PMB</i>	DATE <i>1/26/95</i>	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED <i>WKM</i>	<i>1/26/95</i>	TITLE: <i>LAMP SPECIFICATIONS FOR 01274</i>			
BASIC DIMENSION	.XX	.XXX	APPROVED <i>RAD</i>	<i>1/26/95</i>				
UP TO 6	±.02	±.005	REL. FOR PROD. <i>DAB</i>	<i>1/31/95</i>	CODE IDENT <i>64475</i>		DRAWING NO. <i>16300334</i>	REV.
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		SCALE		SHEET OF	
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								