

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300379		A
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL
A	CURRENT - .590 WAS .570; LIFE - 15 HRS WAS 30	3-2159	6/10/99	DAB

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT
TUNGSTEN HALOGEN REGENERATIVE CYCLE
MINIATURE TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

✱ 2.80 ±.01 VOLTS D.C.

3. CURRENT

.590 ±5% AMPERES

4. COLOR TEMPERATURE

3280 °K AT FILAMENT CENTER
COILS OUTER DIAMETER USING A
TELESCOPING OPTICAL PYROMETER

5. MEAN SPHERICAL CANDLEPOWER

1.70 ±15% MSCP (LAMP MEASURED
IN A 20" INTEGRATING SPHERE)


6. DESIGN LIFE

15 HOURS AVERAGE (LAB RATED)

7. LIGHT CENTER LENGTH

.768 ±.020 L.C.L.

✱ 2.80 VOLTS IS THE NOMINAL VOLTAGE (4) EVEREADY ALKALINE "AAA"
CELLS PROVIDE WHEN OPERATING THIS LAMP AFTER 5 MINUTES WITH
THE CELLS ARRANGED IN A SERIES/PARALLEL CONFIGURATION
(EACH LEG OF THE PARALLEL CIRCUIT CONSISTS OF (2) CELLS IN SERIES)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB	DATE 5/17/96	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED WKM	5/23/96	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01284			
BASIC DIMENSION	.XX	.XXX	APPROVED RAD	5/22/96				
UP TO 6	±.02	±.005	REL. FOR PROD. DAB	5/23/96	CODE IDENT 64475		DRAWING NO. 16300379	REV. A
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		SCALE		SHEET OF	
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								