


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300394		A
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL
A	RELEASE TO PRODUCTION	3-1587	10/25/96	DAB

1. LAMP TYPE	LENSED END, C-6 FILAMENT, TUNGSTEN HALOGEN REGENERATIVE CYCLE, MINIATURE TWO-PIN CONSTRUCTION
2. RATED VOLTAGE	6.00 ±.01 VOLTS D.C.
3. CURRENT	3.35 ±5% AMPERES
4. COLOR TEMPERATURE	3325 °K AT FILAMENT CENTER COILS OUTER DIAMETER USING A TELESCOPING OPTICAL PYROMETER
5. MEAN SPHERICAL CANDLEPOWER	37.0 ±12% MSCP (WIRE TERMINAL LAMP IN A 20" INTEGRATING SPHERE)
6. DESIGN LIFE	100 HOURS AVERAGE (LAB RATED)
7. SPOT SIZE	.195" NOMINAL DIA. MEASURED IN A TRANSVERSE PLANE TANGENT TO THE LENS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB	DATE 10/22/96	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED WKM	10/22/96	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01295			
BASIC DIMENSION	.XX	.XXX	APPROVED RAD	10/22/96				
UP TO 6	±.02	±.005	REL. FOR PROD. DAB	10/23/96	CODE IDENT 64475		DRAWING NO. 16300394	REV. A
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		SCALE		SHEET OF	
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								