


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300450		A
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL
A	RELEASE TO PROD.	3-1963	7/8/98	CNS

1. LAMP TYPE	HEMISPHERICAL END, C-6 FILAMENT, TUNGSTEN HALOGEN REGENERATIVE CYCLE, MINIATURE TWO-PIN CONSTRUCTION
2. RATED VOLTAGE	6.00 ±.01 VOLTS D.C.
3. CURRENT	1.67 ±5% AMPERES
4. COLOR TEMPERATURE	3230 °K AT FILAMENT CENTER COILS OUTER DIAMETER USING A TELESCOPING OPTICAL PYROMETER
5. MEAN SPHERICAL CANDLEPOWER	18.75 ±12% MSCP (WIRE TERMINAL LAMP IN A 20" INTEGRATING SPHERE)
6. DESIGN LIFE	85 HOURS AVERAGE (LAB RATED)
7. LIGHT CENTER LENGTH	.842 ±.007 L.C.L.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN P BARAN	DATE 6/18/98	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED R GABAK	7/7/98				
BASIC DIMENSION	.XX	.XXX	APPROVED R DEAN	7/6/98	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01316			
UP TO 6	±.02	±.005	REL. FOR PROD. C STEWART	7/8/98				
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		CODE IDENT 64475		DRAWING NO. 16300450	REV. A
ABOVE 24	±.06	±.015			SCALE			
ANGLES ± 1/2 DEGREE								SHEET OF