



**PATENTED**

**CUSTOMER APPROVAL**  
 BY: \_\_\_\_\_  
 DATE: \_\_\_\_\_

**"ANDON PROPRIETARY INFORMATION"**

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO ANDON ELECTRONICS CORPORATION. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED AS ANDON ELECTRONICS MAY OTHERWISE AGREE IN WRITING.

**TECHNICAL INFORMATION**

**HEAT SINK:** ALUMINUM  
**INSULATOR:** FR-4 (EPOXY)  
**TERMINAL CONTACT:** BRASS, PER ASTM-B16, **PLATED:** GOLD 10μ INCHES MIN. BeCu, PER ASTM-B194, **PLATED:** GOLD 10μ INCHES MIN.  
**FORCES:** INSERTION: 1.24 oz. (35 GRAMS) MAX. PER PIN  
 WITHDRAWAL: 0.5 oz. (14 GRAMS) MIN. PER PIN

**TERMINAL ACCEPTS:** 0.015" [.38mm] – 0.021" [.53mm] PINS

**RoHS COMPLIANT**

<b>AEAC ANDON ELECTRONICS CORP.</b> 4 COURT DRIVE LINCOLN, RI. 02865, USA		
TITLE: .200 [5.08] PIN CIRCLE, 6 PIN, FP#1006-02 FLANGE SENSOR HEAT SINK SOCKET		
TOLERANCE EXCEPT AS NOTED	DRAWN BY: A.D.GRIMM	SCALE: NONE
ANGLE ... ± 2'	CHK'D BY: FE/ADG	DATE: 12/20/18
FRACTION ±.010 .XX ..... ±.010 .XXX ..... ±.005	APP'D BY: F. ESTRADA	FILE:
	UNITS: INCHES [MILLIMETERS]	

REV.	DESCRIPTION	DATE	REV. BY	APP. BY	A DWG. NO. F200-1006-02-274K-R27-L14-HS1	REV. 0
------	-------------	------	---------	---------	---	-----------