



SECTION A-A
-01S

CUSTOMER APPROVAL
BY: _____
DATE: _____

TECHNICAL INFORMATION

INSULATOR: BLACK FR-4 (EPOXY)

TERMINAL: BRASS, PER ASTM-B16

CONTACT: BeCu, PER ASTM-B194

FORCES: INSERTION: 9.0 oz. - 255 GRAMS AVG. WITH A .018" [0.46] DIA. PIN
 WITHDRAWAL: 2.0 oz. - 56 GRAMS AVG. WITH A .018" [0.46] DIA. PIN

PLATING: CONTACT: GOLD 10μ INCHES MIN.
 TERMINAL: GOLD 10μ INCHES MIN.

TERMINAL ACCEPTS: ∅.016" [.40mm] - ∅.022" [.56mm] PINS

"ANDON PROPRIETARY INFORMATION"

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO ANDON ELECTRONICS CORPORATION. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED AS ANDON ELECTRONICS MAY OTHERWISE AGREE IN WRITING.



TITLE: .200 [5.08] PIN CIRCLE 4 PIN FP 01T
 ROUND SENSOR SOCKET w/TAB

TOLERANCE EXCEPT AS NOTED	DRAWN BY: F. MARTINS	SCALE: 6:1
ANGLE ... ± 2°	CHK'D BY: FE /AG	DATE: 04/03/13
FRACTION ±.010	APP'D BY: F. ESTRADA	FILE:
.XX ±.010		
.XXX ±.005		
	UNITS: INCHES [MILLIMETERS]	

RoHS COMPLIANT

REV.	DESCRIPTION	DATE	REV. BY	APP. BY	A DWG. NO. R200-0404-01T-01S-R27-L14	REV. 0
------	-------------	------	---------	---------	--------------------------------------	--------