


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300288		A
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL
A	LIGHT OUTPUT - 90 FOOTCANDLES WAS 113	3-1253	8/18/94	DAB

1. LAMP TYPE	REFLECTORIZED LAMP (PARABOLIC), C-6 FILAMENT, HALOGEN REGENERATIVE CYCLE
2. RATED VOLTAGE	12.00 ±.01 VOLTS D.C.
3. CURRENT	1.67 ±5% AMPS
4. COLOR TEMPERATURE	3000 °K AT FILAMENT CENTER COILS OUTER DIAMETER USING A TELESCOPING OPTICAL PYROMETER
5. MEAN SPHERICAL CANDLEPOWER	25.0 ±12% MSCP (WIRE TERMINAL LAMP IN A 20" INTEGRATING SPHERE
6. DIVERGENCE ANGLE	DIVERGENCE 9° ±2° AT GREATER THAN 48" FROM REFLECTOR RIM
7. END LIGHT OUTPUT	A. WITH THE REFLECTOR RIM 48" FROM THE COSINE SURFACE OF THE EG&G COSINE PHOTOMETRIC PROBE, THE LIGHT OUTPUT SHALL BE A MINIMUM OF 90 FOOTCANDLES. THIS MEASUREMENT SHALL BE PERFORMED USING AN EG&G MODEL 550 RADIOMETER/PHOTOMETER SYSTEM EQUIPPED WITH A 550-18 COSINE PHOTOMETRIC PROBE B. DARK CENTER IN LIGHT SPOT VISUALLY DISAPPEARS AT 6 TO 12" FROM REFLECTOR RIM
8. DESIGN LIFE	2000 HOURS AVERAGE (LAB RATED) TESTED IN AMBIENT AIR WITH G4 SOCKET AS ONLY HEAT SINK. RECOMMENDED MAXIMUM HEAT SINK IS .5 IN ³ AL WITH 4 IN ² AREA
9. SPOT SIZE	2*(d*TAN(A/2)) = SPOT DIAMETER IN INCHES d = DISTANCE FROM REFLECTOR RIM TO TARGET PLANE A = DIVERGENCE ANGLE SPOT SIZE IS DETERMINED BY POINT AT WHICH 50% OF CENTER INTENSITY IS REACHED. CALCULATION GOOD FOR GREATER THAN 48" FROM REFLECTOR RIM

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB	DATE 4/21/94	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED RAD	4/27/94	TITLE: LAMP SPECIFICATIONS FOR 8208-001			
BASIC DIMENSION	.XX	.XXX	APPROVED WKM	4/27/94				
UP TO 6	±.02	±.005	REL. FOR PROD. DAB	5/9/94	CODE IDENT 64475		DRAWING NO. 16300288	REV. A
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		SCALE		SHEET OF	
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								