

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300235		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

LENSED END, C-6 FILAMENT, GAS FILLED,
SUBMINIATURE TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

3.50 ±.01 VOLTS D.C.

3. CURRENT

.575 ±5% AMPERES

4. COLOR TEMPERATURE

3050 °K AT FILAMENT CENTER COILS OUTER
DIAMETER USING A TELESCOPING OPTICAL
PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


1.65 ±12% MSCP (WIRE TERMINAL LAMP IN A
20" INTEGRATING SPHERE)

6. DESIGN LIFE

400 HOURS AVERAGE

7. SPOT SIZE

.140" NOMINAL DIA. TANGENT TO THE LENS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB	DATE	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.				
TOLERANCES ON:					CHECKED		TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01207		
BASIC DIMENSION	.XX	.XXX	APPROVED						
UP TO 6	±.02	±.005			REL. FOR PROD.				
ABOVE 6 TO 24	±.03	±.010							
ABOVE 24	±.06	±.015	DO NOT SCALE		CODE IDENT		DRAWING NO.	REV.	
ANGLES ± 1/2 DEGREE					64475		16300235		
					SCALE			SHEET	OF