

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300243		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT, GAS FILLED,
SUBMINIATURE TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

3.5 ±.01 VOLTS D.C.

3. CURRENT

.575 ±5% AMPERES

4. COLOR TEMPERATURE

3050 °K AT FILAMENT CENTER COILS OUTER
DIAMETER USING A TELESCOPING OPTICAL
PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


1.65 ±12% MSCP (WIRE TERMINAL LAMP IN A
20" INTEGRATING SPHERE)

6. DESIGN LIFE

400 HOURS AVERAGE

7. LIGHT CENTER LENGTH

.610 ±.020 L.C.L.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB		DATE		WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED				TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01217			
BASIC DIMENSION	.XX	.XXX	APPROVED							
UP TO 6	±.02	±.005	REL. FOR PROD.				CODE IDENT		DRAWING NO.	REV.
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE				64475	16300243		
ABOVE 24	±.06	±.015					SCALE			
ANGLES ± 1/2 DEGREE										