


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300245		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE	HEMISPHERICAL END, C-6 FILAMENT, GAS FILLED, SUBMINIATURE TWO-PIN CONSTRUCTION
2. RATED VOLTAGE	5.0 ±.01 VOLTS D.C.
3. CURRENT	.97 ±5% AMPERES
4. COLOR TEMPERATURE	2800 °K AT FILAMENT CENTER COILS OUTER DIAMETER USING A TELESCOPING OPTICAL PYROMETER
5. MEAN SPHERICAL CANDLEPOWER	3.3 ±12% MSCP (WIRE TERMINAL LAMP IN A 20" INTEGRATING SPHERE)
6. DESIGN LIFE	10,000 HOURS AVERAGE
7. LIGHT CENTER LENGTH	.610 ±.020 L.C.L.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB		DATE 2/4/93		WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED CFC		2/4/93		TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01219			
BASIC DIMENSION	.XX	.XXX	APPROVED JWH		2/16/93					
UP TO 6	±.02	±.005	REL. FOR PROD. DAB		2/16/93		CODE IDENT 64475		DRAWING NO. 16300245	REV.
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE			SCALE		SHEET OF		
ABOVE 24	±.06	±.015								
ANGLES ± 1/2 DEGREE										