

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300266		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT
GAS FILLED, SUBMINIATURE TWO-PIN
CONSTRUCTION

2. RATED VOLTAGE

3.50 ±.01 VOLTS D.C.

3. CURRENT

.575 ±5% AMPS

4. COLOR TEMPERATURE


3120 °K AT FILAMENT CENTER COILS
OUTER DIAMETER USING A TELESCOPING
OPTICAL PYROMETER

5. MEAN SPHERICAL CANDLEPOWER

1.90 ±12% MSCP (WIRE TERMINAL LAMP
IN A 20" INTEGRATING SPHERE)

6. DESIGN LIFE

250 HOURS AVERAGE (LAB RATED)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN <i>PMB</i>	DATE <i>10/21/93</i>	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED <i>RAD</i>	<i>10/21/93</i>	TITLE: <i>LAMP SPECIFICATIONS FOR SK-DAB-01251</i>			
BASIC DIMENSION	.XX	.XXX	APPROVED <i>DAB</i>	<i>10/21/93</i>				
UP TO 6	±.02	±.005	REL. FOR PROD. <i>DAB</i>	<i>10/21/93</i>				
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		CODE IDENT 64475		DRAWING NO. <i>16300266</i>	REV.
ABOVE 24	±.06	±.015			SCALE			SHEET
ANGLES ± 1/2 DEGREE								