

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300175		A
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL
A	REMOVED LIGHT CENTER LENGTH SPEC	3-1052	2/16/93	DAB

1. LAMP TYPE

FLAME FORMED LENSED END, C-6 FILAMENT, TUNGSTEN HALOGEN REGENERATIVE CYCLE, SUBMINIATURE TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

3.65 ±.01 VOLTS D.C.

3. CURRENT

.980 ±5% AMPERES

4. COLOR TEMPERATURE

3240 °K AT FILAMENT CENTER COILS OUTER DIAMETER USING A TELESCOPING OPTICAL PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


4.0 ±12% MSCP (WIRE TERMINAL LAMP IN A 20" INTEGRATING SPHERE)

6. DESIGN LIFE

45 HOURS AVERAGE

7. SPOT SIZE

.140" NOMINAL DIA. TANGENT TO THE LENS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN LAW	DATE 8/22/89	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED JWH	8/29/89				
BASIC DIMENSION	.XX	.XXX	APPROVED DAB	9/28/89	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01093			
UP TO 6	±.02	±.005	REL. FOR PROD. DAB	9/28/89				
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		CODE IDENT 64475		DRAWING NO. 16300175	REV. A
ABOVE 24	±.06	±.015			SCALE			
ANGLES ± 1/2 DEGREE							SHEET	OF