

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300236		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

LENSED END, C-6 FILAMENT, TUNGSTEN
HALOGEN REGENERATIVE CYCLE,
SUBMINIATURE TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

2.60 ±.01 VOLTS D.C.

3. CURRENT

.850 ±5% AMPERES

4. COLOR TEMPERATURE

2840 °K AT FILAMENT CENTER COILS OUTER
DIAMETER USING A TELESCOPING OPTICAL
PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


.95 ±12% MSCP (WIRE TERMINAL LAMP IN A
20" INTEGRATING SPHERE)

6. DESIGN LIFE

4000 HOURS AVERAGE

7. SPOT SIZE

.140" NOMINAL DIA. TANGENT TO THE LENS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB		DATE		WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED				TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01208			
BASIC DIMENSION	.XX	.XXX	APPROVED							
UP TO 6	±.02	±.005	REL. FOR PROD.				CODE IDENT		DRAWING NO.	REV.
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE				64475		16300236	
ABOVE 24	±.06	±.015					SCALE			
ANGLES ± 1/2 DEGREE										