


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300135		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE	HEMISPHERICAL END, C-6 FILAMENT, TUNGSTEN HALOGEN REGENERATIVE CYCLE
2. RATED VOLTAGE	2.80 ±.01 VOLTS D.C.
3. CURRENT	.850 ±5% AMPERES
4. COLOR TEMPERATURE	3300 °K AT FILAMENT CENTER COILS OUTER DIAMETER USING A TELESCOPING OPTICAL PYROMETER
5. MEAN SPHERICAL CANDLEPOWER	2.63 ±12% MSCP (WIRE TERMINAL LAMP IN A 20" INTEGRATING SPHERE)
8. DESIGN LIFE	15 HOURS AVERAGE (LAB RATED)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN <i>PMB</i>	DATE	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED <i>JWH</i>	11/2/87	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01080			
BASIC DIMENSION	.XX	.XXX	APPROVED <i>DAB</i>	12/7/87	CODE IDENT 64475		DRAWING NO. 16300135	REV.
UP TO 6	±.02	±.005	REL. FOR PROD. <i>DAB</i>	12/7/87	SCALE		SHEET OF	
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE					
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								