

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300281		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

LENSED END, C-6 FILAMENT, TUNGSTEN
HALOGEN REGENERATIVE CYCLE

2. RATED VOLTAGE

3.50 ±.01 VOLTS D.C.

3. CURRENT

.720 ±5% AMPERES

4. COLOR TEMPERATURE

3250 °K AT FILAMENT CENTER COILS OUTER
DIAMETER USING A TELESCOPING OPTICAL
PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


2.70 ±12% MSCP (WIRE TERMINAL LAMP IN A
20" INTEGRATING SPHERE)

6. SPOT SIZE

.125 NOMINAL DIAMETER MEASURED IN A
TRANSVERSE PLANE TANGENT TO THE LENS

7. DESIGN LIFE

20 HOURS AVERAGE (LAB RATED)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB		DATE 1/31/94		WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED RAD		2/1/94		TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01260			
BASIC DIMENSION	.XX	.XXX	APPROVED DAB		2/1/94					
UP TO 6	±.02	±.005	REL. FOR PROD. DAB		2/1/94		CODE IDENT 64475		DRAWING NO. 16300281	REV.
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE			SCALE		SHEET OF		
ABOVE 24	±.06	±.015								
ANGLES ± 1/2 DEGREE										