

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300444		A
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL
A	DRAWING RELEASE	3-1947	6/1/98	DAB

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT,
TUNGSTEN HALOGEN REGENERATIVE CYCLE

2. RATED VOLTAGE

6.00 ±.01 VOLTS D.C.

3. CURRENT

.640 ±5% AMPERES

4. COLOR TEMPERATURE


3050 °K AT FILAMENT CENTER COILS
OUTER DIAMETER USING A TELESCOPING
OPTICAL PYROMETER

5. MEAN SPHERICAL CANDLEPOWER

4.50 ±12% MSCP (WIRE TERMINAL LAMP IN A
20" INTEGRATING SPHERE)

8. DESIGN LIFE

1000 HOURS AVERAGE (LAB RATED)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN P BARAN	DATE 5/22/98	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED R DEAN	5/28/98				
BASIC DIMENSION	.XX	.XXX	APPROVED D WITTER	5/28/98	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01267			
UP TO 6	±.02	±.005	REL. FOR PROD. D BELL	6/1/98				
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		CODE IDENT 64475		DRAWING NO. 16300444	REV. A
ABOVE 24	±.06	±.015			SCALE			
ANGLES ± 1/2 DEGREE								SHEET OF