

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300498		A
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL
A	RELEASE TO PROD.	3-2347	4/18/00	D BELL

1. LAMP TYPE

T1 1/4 LENSED END, C-6 FILAMENT,
TUNGSTEN HALOGEN REGENERATIVE CYCLE

2. RATED VOLTAGE

5.70 ±.01 VOLTS D.C.

3. CURRENT

.400 ±5% AMPERES

4. COLOR TEMPERATURE

3075 °K AT FILAMENT CENTER COILS
OUTER DIAMETER USING A TELESCOPING
OPTICAL PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


2.10 ±15% MSCP (WIRE TERMINAL LAMP
IN A 20" INTEGRATING SPHERE)

6. DESIGN LIFE

500 HOURS AVERAGE (LAB RATED)

7. SPOT SIZE

.10" NOMINAL DIAMETER MEASURED IN A
TRANSVERSE PLANE TANGENT TO THE LENS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN P BARAN	DATE 4/00	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED S PARKER	4/12/00	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01333			
BASIC DIMENSION	.XX	.XXX	APPROVED R DEAN	4/11/00				
UP TO 6	±.02	±.005	REL. FOR PROD. D BELL	4/18/00	CODE IDENT 64475		DRAWING NO. 16300498	REV. A
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		SCALE		SHEET OF	
ABOVE 24	±.06	±.015						
ANGLES ± 1/2 DEGREE								