

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300367		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT, TUNGSTEN HALOGEN REGENERATIVE CYCLE
2. RATED VOLTAGE


8.00 ±.01 VOLTS D.C.
3. CURRENT

2.12 ±5% AMPERES
4. COLOR TEMPERATURE

2950 °K AT FILAMENT CENTER COILS OUTER DIAMETER USING A TELESCOPING OPTICAL PYROMETER
5. MEAN SPHERICAL CANDLEPOWER

17.5 ±15% MSCP (WIRE TERMINAL LAMP IN A 20" INTEGRATING SPHERE)
6. DESIGN LIFE

2500 HOURS AVERAGE (LAB RATED)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN	DATE	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.				
TOLERANCES ON:			PMB	1/31/96					
BASIC DIMENSION	.XX	.XXX	CHECKED	WKM	2/1/96	TITLE: LAMP SPECIFICATION FOR SK-DAB-01068			
UP TO 6	±.02	±.005	APPROVED	RAD	1/31/96				
ABOVE 6 TO 24	±.03	±.010	REL. FOR PROD.	DAB	2/2/96				
ABOVE 24	±.06	±.015	DO NOT SCALE			CODE IDENT 64475		DRAWING NO. 16300367	REV.
ANGLES ± 1/2 DEGREE						SCALE		SHEET OF	