

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300346		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

HEMISPHERICAL END, C-6 FILAMENT,
TUNGSTEN HALOGEN REGENERATIVE CYCLE

2. RATED VOLTAGE

12.00 ±.01 VOLTS, D.C.

3. CURRENT

1.67 ±5% AMPS

4. COLOR TEMPERATURE


3000 °K AT FILAMENT CENTER COILS
OUTER DIAMETER USING A TELESCOPING
OPTICAL PYROMETER

5. MEAN SPHERICAL CANDLEPOWER

25.0 ±12% MSCP (WIRE TERMINAL LAMP
IN A 20" INTEGRATING SPHERE)

6. DESIGN LIFE

2,000 HOURS AVE. (LAB RATED)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN PMB	DATE 7/26/95	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.				
TOLERANCES ON:			CHECKED WKM	7/27/95	TITLE: LAMP SPECIFICATIONS FOR SK-DAB-01273				
BASIC DIMENSION	.XX	.XXX	APPROVED RAD	7/26/95	CODE IDENT 64475		DRAWING NO. 16300346	REV.	
UP TO 6	±.02	±.005	REL. FOR PROD. DAB	7/27/95	SCALE			SHEET OF	
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE						
ABOVE 24	±.06	±.015							
ANGLES ± 1/2 DEGREE									