


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED, OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT OR DEVICES WITHOUT WRITTEN PERMISSION.

16300154

REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

- | | |
|-------------------------------|---|
| 1. LAMP TYPE | LENSED END, C-6 FILAMENT, TUNGSTEN HALOGEN REGENERATIVE CYCLE, MINIATURE TWO-PIN CONSTRUCTION |
| 2. RATED VOLTAGE | 12.00 ±.01 VOLTS, D.C. |
| 3. CURRENT | 1.67 ±5% AMPS |
| 4. COLOR TEMPERATURE | 3000 °K AT FILAMENT CENTER COILS
OUTER DIAMETER USING A TELESCOPING OPTICAL PYROMETER |
| 5. MEAN SPHERICAL CANDLEPOWER | 25.0 ±12% MSCP (WIRE TERMINAL LAMP IN A 20" INTEGRATING SPHERE) |
| 8. DESIGN LIFE | 2000 HOURS AVE. (LAB RATED) |
| 7. OVERALL LENGTH | .981 ±.030 |
| 6. SPOT SIZE | .195 NOMINAL DIAMETER MEASURED IN A TRANSVERSE PLANE TANGENT TO THE LENS |

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN	DATE	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			PMB					
BASIC DIMENSION	.XX	.XXX	CHECKED	8/4/88	TITLE: LAMP SPECIFICATION FOR SK-DAB-01149			
UP TO 6	±.02	±.005	MCA					
ABOVE 6 TO 24	±.03	±.010	APPROVED	8/12/88	CODE IDENT  DRAWING NO. 16300154 REV.			
ABOVE 24	±.06	±.015	DAB					
ANGLES ± 1/2 DEGREE			REL. FOR PROD.	8/12/88	SCALE			
			DAB		SHEET OF			
			DO NOT SCALE					