




D-105-RC-S / D-105-RC-R / D-035-RC-R New generation solid-state photomultipliers

D-105-RC-S / D-105-RC-R / D-035-RC-R – Specification (preliminary)



The new-type solid state photomultipliers D-105-RC-S, D-105-RC-R and D-035-RC-R have been developed to replace APD in detection and measurement of short light pulses in the near-infrared wavelength range. They combine wide dynamic range and resistance to background illumination of APD with high threshold sensitivity and speed of SiPM. They are well-suited for LiDAR, PET and other pulse-detection applications.

Features

- ~ High threshold sensitivity
- ~ Mild operating voltage (60-70 V)
- ~ Wide dynamic range
- ~ CMOS-compatible technology
- ~ Tolerance to background illumination
- ~ Array/matrix capability

Structure

Parameter	Symbol	D-105-RC-S	D-105-RC-R	D-035-RC-R	Unit
Photosensitive area	-	1×1 (square)	∅1 (round)	∅0.3 (round)	mm
Number of cells	-	4.6·10 ⁴	3.6·10 ⁴	3.2·10 ³	-
Cell pitch	-	5			µm
Geometrical fill factor	-	> 90			%
Package	-	capless TO5 covered with optical encapsulant			-
Encapsulant refractive index	-	1.4			-

Absolute maximum ratings

Parameter	Symbol	D-105-RC-S	D-105-RC-R	D-035-RC-R	Unit
Operating conditions	T _{opr}	-40 to +40°C, no condensation			-
Soldering conditions	T _{sol}	350°C max once, 3 s max, at least 1 mm away from lead root			-

Electrical and optical characteristics (T_a = 25°C)


Parameter	Symbol	D-105-RC-S	D-105-RC-R	D-035-RC-R	Unit
Spectral response range	λ	400..900			nm
Peak sensitivity wavelength	λ _p	650			nm
Photon detection efficiency (fast*)	PDE	@650nm: > 30 @905nm: > 10			%
Gain	M	> 5·10 ³			-
Crosstalk probability	p _{ct}	< 1			%
Threshold sensitivity**	S	@905nm: < 200			photons
Single-photon jitter (FWHM)	Δt _{jitter, 1ph}	< 450			ps
Terminal capacitance	C _t	20	16	4	pF

Operating voltage	V_{op}	60-70 (see test ticket)			V
Dark current, typical	$I_{dark,typ}$	5-20	3-15	0.5-1.5	μA
Dark current, max	$I_{dark,max}$	30			μA
Gain temperature factor (on constant voltage)	dM/dT	< 150			$^{\circ}C^{-1}$
Voltage temperature factor (on constant gain)	dV_{op}/dT	< 35			mV/ $^{\circ}C$


* affecting photoresponse amplitude at 1GHz bandwidth

** detection probability $\geq 90\%$, false detection rate ≤ 1 kHz, 1GHz bandwidth, room temperature

Spectral response (typical, see test ticket)




Dimensional outline (side view, unit: mm)




(Some devices are shipped with shortened pins.)

Connection polarity (top view)



Connection example




Typical pulse parameters

(In connection scheme shown above, $\lambda=442\text{nm}$)

Parameter	Symbol	D-105-RC-S	D-105-RC-R	D-035-RC-R	Unit
Rise time (10% to 90%)	t_{rise}	0.42		0.33	ns
Fall time (90% to 10%)	t_{fall}	1.37		0.30	ns

Pulse shape for D-105-RC-S



Document Revision: 2019060301

This page intentionally left blank.