


FLL Series Red Laser Line Module

Part No: FLL5-3.5P-650-**



Product Features

- High Stability and low noise
- Fixed focus
- Reverse Polarity Protection
- Low Cost

Application

- Measurement
- Automation
- Alignment

Mechanical Drawing



Operational Hazard-Semiconductor Laser Diode Module: This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage.

Limited Warranty: One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.

Specification

OPTICAL

Wavelength	650 nm
Optical Output Power (net)	3.5 mW
Stability	<1%
Wavelength Drift	0.2nm/°C
Laser Operation	Continuous
Laser Structure	Single Mode Laser
Focus Distance	Collimated; fixed
Minimum Line Thickness	< 2mm up to 3 meter

ELECTRICAL

Operating Voltage ¹	3 to 5 VDC
Operating Current	<40 mA
Control Circuit	Auto Power Control
Electrical Connections	+Red, -Black

MECHANICAL

Dimension	9mm(Dia) x 25mm(L)
Cable	380mm
Operating Temperature	-10°C to +50°C
Storage Temperature	-40°C to +80°C
Heat Sink Requirements ²	Recommended for extended use

Notes

1. Please ensure there is no voltage or current surge
2. Heat Sink: The FLL Series Red Laser Line Module is designed to dissipate heat through its body. Do not restrict air circulation around the device; an additional heat sink can be used to maximize the performance and life time of the laser.

Caution: The case is internally connected to the circuit and is positive; please do not connect the case to the ground.



Complies with CDRH 21CFR 1040.10

World Star Tech.

185 Konrad Crescent Markham, ON L3R 8T9 Canada
Tel: (416) 363-3332 Fax: (416) 363-3112 www.worldstartech.com




ISO9001:2000 Registered



FLL Series Red Laser Line Module

Part No: FLL5-3.5P-650-**

Fan Angle Selection Guide



L: Line Length

D: Distance

a: Factor

For given Fan Angle, the Line Length **L** at distance **D** is calculated using the equation :

$$L = a \times D$$

For Example: using 4 ° Fan Angle at distance of 1.5m, the Line Length will be $L = 0.07 \times 1.5\text{m} = 0.105\text{m}$;

Part No.	Fan angle	Factor a	Line Length(m)			Laser Class
			D=0.5m	D=1m	D=3m	
FLL5-3.5P-650-04	4 °	0.07	0.04	0.07	0.21	IIIA
FLL5-3.5P-650-15	15°	0.26	0.13	0.26	0.78	II
FLL5-3.5P-650-30	30 °	0.54	0.27	0.54	1.62	II
FLL5-3.5P-650-45	45°	0.83	0.42	0.83	2.49	II
FLL5-3.5P-650-75	75 °	1.53	0.77	1.53	4.59	II