



"ANDON PROPRIETARY INFORMATION"
 THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO ANDON ELECTRONICS CORPORATION. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED AS ANDON ELECTRONICS MAY OTHERWISE AGREE IN WRITING.



TECHNICAL INFORMATION

INSULATORS: BLACK FR-4 LAMINATE
TERMINAL: BRASS, PER ASTM-B16, **PLATED:** GOLD 10 μ INCHES MIN.
CONTACT: BeCu, PER ASTM-B194, **PLATED:** GOLD 10 μ INCHES MIN.
FORCES: INSERTION: 1.24 oz. (35 GRAMS) MAX. PER PIN
 WITHDRAWAL: 0.5 oz. (14 GRAMS) MIN. PER PIN

TERMINAL ACCEPTS: $\phi.015$ " [.38mm] - $\phi.021$ " [.53mm] PINS

RoHS COMPLIANT

TITLE: **.200 [5.08] PIN CIRCLE, 6 PIN, FP#1006-02 FLANGE SENSOR THRU-HOLE SOCKET**

TOLERANCE EXCEPT AS NOTED	DRAWN BY: A.D.GRIMM	SCALE: NONE
ANGLE $\pm 2^\circ$	CHK'D BY: FE/ADG	DATE: 11-16-16
FRACTION $\pm.010$	APP'D BY: F.ESTRADA	FILE:
.XX $\pm.010$	UNITS: INCHES [MILLIMETERS]	
.XXX $\pm.005$		

1	ADD ANGLES PER ECN 01306	12/06/18	GB	ADG
REV.	DESCRIPTION	DATE	REV. BY	APP. BY

DWG. NO. **F200-1006-02-274K-R27-L14** REV. **1**